

★BIOS- P31;S05 2001-316041/33 ★WO 200119249-A1
Drowsiness monitoring method e.g. for car driver, pilot, involves triggering alarm if specific parameters representing state of autonomous nervous system of driver exceeds preset threshold value (Eng)

BIOSYS AB 2000.03.31 2000US-540902 (1999.09.14 1999SE-003270)

W06 X14 X22 (2001.03.22) A61B 5/18, A61B 5/0205

2000.09.13 2000WO-SE01771 N(AE AG AL AM AT AU AZ BA BB BG BR
BY BZ CA CH CN CR CU CZ DE DK DM DZ EE ES FI GB GD GE GH GM
HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD
MG MK MN MW MX MZ NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM
TR TT TZ UA UG UZ VN YU ZA ZW) R(AT BE CH CY DE DK EA ES FI FR
GB GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TZ
UG ZW)

Novelty: A parameter reflecting state of autonomic nervous system, for e.g. cardiac activity of driver (403), is recorded by sensors (401). If parameter fulfills certain criteria alarm is triggered by generator (407) and another parameter reflecting respiratory and/or body movement patterns is monitored. If both the monitored parameter exceeds threshold level, alarm is generated to indicate risk of driving a car.

Detailed Description: An INDEPENDENT CLAIM is also included for drowsiness monitoring system for car drivers.

Use: For detecting drowsiness of car drivers, monitoring personnel of nuclear power plant or radar office, pilot, etc.

Advantage: The monitoring procedure is more reliable and user friendly as cardiac and respiratory functions of person are used to detect condition of drowsiness.

Description of Drawing(s): The figure shows the view of system for detecting drowsiness of person driving a car.

Sensor 401


Driver 403

Alarm generating device 407

(13pp Dwg.No.1/2)

N2001-227214

S05-D01C5A; W06-B01B; W06-B02E; X14-C05X; X22-E04



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
22 March 2001 (22.03.2001)

PCT

(10) International Publication Number
WO 01/19249 A1

- (51) International Patent Classification⁷: A61B 5/18, 5/0205
- (21) International Application Number: PCT/SE00/01771
- (22) International Filing Date:
13 September 2000 (13.09.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
9903270-8 14 September 1999 (14.09.1999) SE
09/540,902 31 March 2000 (31.03.2000) US
- (71) Applicant: BIOSYS AB [SE/SE]; Box 237, S-421 23 Västra Frölunda (SE).
- (72) Inventor: BADER, Gaby; Lilla Danska vägen 12, S-412 74 Göteborg (SE).
- (74) Agents: SANDSTRÖM, Staffan et al.; Bergenstråhle & Lindvall AB, Box 17704, S-118 93 Stockholm (SE).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— With international search report.
— Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: A METHOD AND A SYSTEM FOR MONITORING A PERSON



(57) Abstract: In a method and a system the autonomic nervous system, and in particular parameters reflecting the current condition of the autonomic nervous system, are monitored for detecting a lower level of wakefulness. One such parameter, which has been found to indicate such a state, is cardiac oscillation. Thus, the autonomic nervous system affects the heartbeat of person falling to sleep in such a way that the heartbeat will go through a series of acceleration and de-acceleration.

WO 01/19249 A1

WO 01/19249

1

PCT/SE00/01771

A METHOD AND A SYSTEM FOR MONITORING A PERSON

TECHNICAL FIELD

The present invention relates to a method and a system for monitoring a person. In particular the present invention relates to a method and a system for monitoring drowsiness of a person performing a task where it is important to be awake, such as a person driving a car, monitoring personnel in a nuclear power plant or in a radar office, or a pilot.

BACKGROUND OF THE INVENTION AND PRIOR ART

In today's traffic, there is a problem relating to people driving vehicles despite the fact that they are too tired, sleepy or drowsy in order to safely drive their vehicle. In particular, during longer journeys, a person may start the journey in good shape and then as times goes being more and more drowsy, and, in the worst case, finally go to sleep. Such a scenario is of course highly undesirable, since it poses a great threat to both the driver and persons around him/her, such as other drivers or passengers in vehicles on the same road.

Also, it is known that when a person becomes drowsy, the eyelid and pupil movement pattern changes. Furthermore, in WO/33403 a method where the corresponding relationship between cardiac and respiratory functions are used in order to detect a condition of drowsiness.

SUMMARY

It is an object of the present invention to provide a method and a system, which have an improved reliability over the prior art. It is also an object of the present invention to provide a method and a system, which is more robust and user friendly compared to the methods according to the prior art.

This object is obtained by means of monitoring the autonomic nervous system, and in particular parameters reflecting the current condition of the autonomic nervous system. Thus, by means of intensive research it has been possible to show that it is in fact a change in state in the autonomic nervous system that causes the body to change certain patterns in, for example, eye movements. Thus, changes in activities in the autonomic nervous system are reflected by changes in behaviour of certain physiological parameters.

WO 01/19249

2

PCT/SE00/01771

In a preferred embodiment the method and system comprise continuous recording of at least one parameter reflecting the current state of the autonomic nervous system, such as a parameter reflecting cardiac activity. If a trend in the monitored parameter fulfils a certain criteria or certain conditions, such as slowing down of the activity, a first alarm level is triggered by the system. At the first alarm level a second parameter reflecting the autonomic nervous system can be monitored in addition of the first parameter, such as body motor activity or respiratory activity. If both the monitored parameters exceed a pre-set threshold value an alarm is generated indicating that there is a risk that the person may fall to sleep. In this manner a multi-step threshold model is formed, which is used to indicate a potential risk of falling asleep.

When such an alarm is generated a number of different actions can be taken. For example, a light or sound signal can be generated, an air puff, or another change in the physical environment, or a vibrator located in the seat where the person is seated can be activated.

The invention relies on the fact that extensive studies have shown that the autonomic nervous system reflects the wakefulness level of a person. Thus, by monitoring a parameter, which reflects the current state of the autonomic nervous system, a lower level of wakefulness can be detected. One such parameter, which has been found to indicate such a state, is cardiac oscillation. Thus, the autonomic nervous system affect the heartbeat of a person falling to sleep in such a way that the heartbeat will go through a series of acceleration and de-acceleration.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will now be described in more detail and with reference to the accompanying drawings, in which:

- Fig. 1 is a general view of a person driving a car.
- Fig. 2 is a flowchart illustrating different steps carried out when detecting a condition of drowsiness.

DETAILED DESCRIPTION

In Fig. 1 a driver 403 in a vehicle 404 is shown. In the vehicle 404 a seat 406 and a safety belt 405 are provided. The seat 406 and the safety belt 405 are provided with sensors 401. The

WO 01/19249

3

PCT/SE00/01771

sensors 401 are adapted to sense physiological parameters from a person, such as the driver 403, sitting in the seat 406.

For example, the sensors may output signals corresponding to respiration, cardiac activity and body movements from the driver. The sensors can be of any kind and are preferably of a conventional type, such as PVF type sensors. The sensors are connected to a data collecting computer unit 402. The unit 402 is operated by software, which uses the input data from the sensors for determining if the driver risk falling asleep. The procedure steps carried out in the unit 402 are described in more detail below in conjunction with Fig. 2.

The computer unit 402 is connected to an alarm-generating unit 407. The alarm unit can comprise several different alarm-generating devices. For example, the unit 407 can comprise a siren, a light emitting device, a vibrator etc. If the alarm unit is connected to a vibrator the vibrator can be located in the seat 406 or at some other suitable location. The object of the alarm unit is to indicate to the driver when he/she risks falling asleep, and thereby preventing that the driver become drowsy or falls asleep, which can have serious consequences. For example the alarm can activate the vehicle such as by means of slowing down the speed of the vehicle.

In Fig. 2 a flowchart illustrating different steps carried out by the software in the computer unit 402 for monitoring the driver 403 is shown. The software in the unit 402 continuously updates a first physiological parameter, such as a parameter corresponding to cardiac activity, and in particular the time interval between successive heartbeats.

In the case when the first physiological parameter monitored by the computer unit 402 is the time interval between successive heartbeats, the following process steps can be carried out by the software. First, in a step 201, a mean value of the time between successive heartbeats during a first time interval window is calculated. The first window can have any duration, but in a preferred embodiment, the first time interval window is in the range of 1 – 20 seconds and in particular in the range of 5 – 10 seconds.

Next, in a step 203, a trend in the mean value as calculated in step 201 is read. The trend can, for example, be derived by means of during a second time interval window, being longer than the first time interval window, and continuously recording the changes in the value obtained

WO 01/19249

4

PCT/SE00/01771

in the second window. The duration of the second window can for example be in the range 1 – 10 minutes, and in particular in the range 1 – 3 minutes. In the example given here the duration of the second window is 2 minutes and is updated every 6 second.

In the example given here, where cardiac activity continuously is recorded, the trend in the derived windowed mean value for successive heartbeats is monitored. If the trend exceeds one or several threshold values, the procedure continues to the step 207, and else the procedure returns to the step 201, as is indicated in the step 205.

The threshold value in step 203 can, for example, be set so that if the mean value between successive heartbeats is continuously increasing during a pre-set time interval, the threshold value is exceeded. Other possibilities for the threshold value include zero-crossing and slope values.

The object of setting the threshold value is to detect acceleration in cardiac activity, and in particular to detect a state of successive accelerations and de-accelerations. A pattern corresponding to successive accelerations and de-accelerations is used to indicate that the driver is falling asleep and in order to prevent this an alarm is triggered.

In order to prevent that a false alarm is triggered, the following additional process steps are preferably executed. In the step 207 recording of one or several additional parameter(s) is activated. The additional parameter(s) can be additional physiological parameters, such as respiratory pattern (amplitude and frequency variations) or body motor activity, or other parameters. In the example described herein the additional parameters are physiological parameters. However, it is possible to record physical parameters as well. For example, the vehicle position on the road can be recorded or steering wheel movements can be recorded. Also, it is possible to adjust the alarm levels to different levels for different individuals, in order to further prevent triggering of an alarm at an incorrect time.

If the recorded additional parameters also indicate the same fact, i.e. that it is likely that the autonomic nervous system is in a state where the person is drowsy, the alarm generating unit is activated in a process step 209. The activation of the alarm is performed in order to indicate to the driver that there is a risk of falling asleep. If it is decided that the driver is not likely to fall asleep the process returns to the step 201 as is indicated in step 208.

WO 01/19249

5

PCT/SE00/01771

The alarm generating unit can comprise audio and/or light signals, and means for generating environment conditioning signals. Also a vibrator can be located in the driver seat or the unit can trigger a change in temperature.

Use of the system and method as described herein achieves an improved monitoring of a person whom should stay awake and alert, such as for example a driver of a vehicle, a pilot or a person supervising an industrial process such as supervising personnel at a nuclear power plant. The system can be made very robust and insensitive to minor variations in the physiological parameters monitored by the system and used as input data to the method executing the steps for determining if the monitored person is drowsy or risks falling asleep. Thus, the system is adapted to prevent triggering a false alarm. Also, in order to even further ensure that the triggering of a false alarm is avoided, several parameters can be monitored, both physical and physiological, in the event that a first monitored parameter indicates that the alarm should be triggered. The logic for correlating the outcome of different monitored parameter can either be formed by different logic block or by one single logic block evaluating the combined signal from the different monitored parameters.

WO 01/19249

6

PCT/SE00/01771

Claims:

1. A method of monitoring condition and performance of a person, comprising the steps of:
 - continuously recording at least a first physiological parameter representing the state of the autonomic nervous system,
 - monitoring the trend of said at least first physiological parameter, and
 - if the trend fulfils a certain pre-determined condition, trigger a first alarm level at which first alarm level at least a second parameter is analyzed, and
 - if the first physiological parameter in conjunction with the second parameter exceeds a pre-determined threshold value, trigger an alarm.
2. The method according to claim 1, wherein the monitored condition and performance is wakefulness and /or drowsiness.
3. The method according to any of claims 1 or 2, wherein the alarm comprises a multi-level threshold.
4. A method of monitoring condition and performance of a human comprising the steps of:
 - continuously detecting the presence of successive accelerations and de-accelerations in the cardiac activity, and
 - in response to the detection of the presence of such successive accelerations and de-accelerations in the cardiac activity, indicate that the person risks entering a state of lower wakefulness.
5. The method according to claim 4, wherein respiratory and/or body movement patterns also are analyzed.
6. A system for monitoring condition and performance of a person, comprising :
 - a recording unit for continuously recording at least a first physiological parameter representing the state of the autonomic nervous system,
 - a monitoring device for monitoring the trend of said at least first physiological parameter, and
 - an analyzing unit for triggering a first alarm level at which first alarm level at least a second parameter is analyzed, if the trend fulfils a certain pre-determined condition, and

WO 01/19249

7


PCT/SE00/01771

- an alarm generating unit for triggering an alarm, if the first physiological parameter in conjunction with the second parameter exceeds a pre-determined threshold value.
7. The system according to claim 6, wherein the monitored condition and performance is wakefulness and /or drowsiness.
8. The system according to any of claims 6 or 7, wherein the alarm unit comprises a multi-level threshold.
9. A system for monitoring condition and performance of a human comprising :
- An analyzing unit for continuously detecting the presence of successive accelerations and de-accelerations in the cardiac activity, and
 - an alarm unit arranged to, in response to the detection of the presence of such successive accelerations and de-accelerations in the cardiac activity, indicate that the person risks entering a state of lower wakefulness.
10. The system according to claim 9, wherein respiratory and/or body movement patterns also are analyzed by the analyzing unit .

WO 01/19249

PCT/SE00/01771

1 / 2



WO 01/19249

PCT/SE00/01771

2 / 2




FIG. 2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/01771

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61B 5/18, A61B 5/0205

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5846206 A (GABY BADER), 8 December 1998 (08.12.98) --	1-10
X	US 5813989 A (SATOSHI SAITOH ET AL), 29 Sept 1998 (29.09.98), abstract, figure --	1-10
X	US 5488353 A (YOSHINAKA KAWAKAMI ET AL), 30 January 1996 (30.01.96), abstract, figure --	1-10
A	US 5311877 A (ATSUhide KISHI), 17 May 1994 (17.05.94), abstract, figure --	1-10

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

12 January 2001

Date of mailing of the international search report

15-01-2001

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Hélène Erikson/Els

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/01771

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9321615 A1 (PROMOTIONS S.A.), 28 October 1993 (28.10.93), abstract, claims --	1-10
A	US 4005398 A (NAOHIKO INOUE ET AL), 25 January 1977 (25.01.77), abstract, claims --	1-10
A	US 4706072 A (TAKESHI IKEYAMA), 10 November 1987 (10.11.87), abstract, claims -- -----	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

04/12/00

International application No.
PCT/SE 00/01771

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
US	5846206	A	08/12/98	EP	0764000 A	26/03/97
				SE	508285 C	21/09/98
				SE	9401959 A	08/12/95
				WO	9533403 A	14/12/95
				SE	9500629 D	00/00/00
US	5813989	A	29/09/98	EP	0713675 A	29/05/96
				JP	8140949 A	04/06/96
US	5488353	A	30/01/96	DE	69310702 D,T	25/09/97
				EP	0605902 A,B	13/07/94
				JP	6197890 A	19/07/94
				KR	9705738 B	19/04/97
US	5311877	A	17/05/94	JP	5092039 A	16/04/93
WO	9321615	A1	28/10/93	DE	69320801 D,T	29/04/99
				EP	0638193 A,B	15/02/95
				SE	506716 C	02/02/98
				SE	9201255 A	22/10/93
US	4005398	A	25/01/77	DE	2516675 A	30/10/75
				GB	1476704 A	16/06/77
				JP	1105082 C	16/07/82
				JP	50135738 A	28/10/75
				JP	56048324 B	14/11/81
US	4706072	A	10/11/87	DE	3443644 A	05/06/85
				FR	2555522 A	31/05/85
				GB	2150725 A,B	03/07/85
				GB	8430182 D	00/00/00
				JP	1605496 C	31/05/91
				JP	2030685 B	09/07/90
				JP	60193438 A	01/10/85
				JP	1047175 B	12/10/89
				JP	1570625 C	25/07/90
				JP	60116326 A	22/06/85
				JP	60116327 A	22/06/85
				JP	1047176 B	12/10/89
				JP	1570626 C	25/07/90
				JP	60116328 A	22/06/85
				JP	1604803 C	13/05/91
				JP	2028968 B	27/06/90
				JP	60132537 A	15/07/85
				GB	2171547 A,B	28/08/86
				GB	8604085 D	00/00/00
				JP	1024647 B	12/05/89
				JP	1540254 C	31/01/90
				JP	60135330 A	18/07/85